## Amendments to the Compendium of Classification Opinions –HS Committee 60<sup>th</sup> Session

The following list contains the decisions taken by the Harmonized System Committee (60<sup>th</sup> Session – October 2017) concerning amendments to the Harmonized System Compendium of Classification Opinions, <u>applicable as of 1 January 2018</u>. This publication will be updated regularly.

The Harmonized System Compendium of Classification Opinions (FOURTH EDITION **2017**) is published by WCO and consists of a numerical list, set out in the order of headings and subheadings of the Harmonized Commodity Description and Coding System, of the Classification Opinions adopted by WCO. Within any Harmonized System heading or subheading the Classification Opinions are listed in chronological order. The Compendium is available as a bilingual publication in English and French, the two official languages of the WCO, and can be ordered directly (see "Online Services" > "Bookshop" on this Web site).

The amendments listed below are reproduced in the order of the current pages concerned and will be incorporated into the aforementioned WCO publication in due time by replacing the pages affected by the amendments made.

## Advice

Parties seeking to import or export merchandise covered by a decision are advised to verify the implementation of the decision by the importing or exporting country, as the case may be.

	ı			,
項	HS CODE	編	增	貨品說明
次		號	修	
1	0406.10	2	增	Fresh cheese composed of concentrated, fermented skimmed milk (80
				%), fruit preparation (strawberry) (10 %), sugar (7.6 %), modified
				starch, strawberry seeds, black carrot juice concentrate, natural
				flavouring, thickener, mineral concentrate from milk, lemon juice
				concentrate and acid regulators. It also contains the two cultures
				Lactobacillus bulgaricus and Streptococcus thermophilus. The protein
				content in the dairy part is 9.5 % (8.4 % in the product in total). During
				the production process the product has undergone a gentle "heat
				shock" and a quark separator is used in order to remove the whey. In
				addition, a smoothing process is used to improve the consistency. The
				product is put up for retail sale in a plastic container with a net content
				of 160 g, and consists of two layers – the lower layer being a fruit
				preparation (strawberry), while the upper layer is in the form of a white
				dairy product.
				Application of GIRs 1 and 6.".
1	0406.10	2	增	新鮮起司由濃縮發酵脫脂乳(80%)、調製水果(草莓)(10%)、
				糖(7.6%)、改質澱粉、草莓籽、黑胡蘿蔔濃縮汁、天然香料、增
				稠劑,牛奶中的濃縮礦物質、濃縮檸檬汁和酸度調節劑組成,還含有
				有保加利亞乳桿菌和嗜熱鏈球菌兩種菌。乳製品部分蛋白質含量為
				9.5% (總產品佔比為 8.4%)。生產過程中產品經歷了溫和的"熱衝

項次	HS CODE	編號	增修	貨品說明
		3///	19	题",并且使用太太(guardy)八种昭市上队创建。 日外,利用亚温4。
				擊",並且使用夸克(quark)分離器來去除乳清。另外,利用平滑加工(amagthing process) 始末去增加多日遭知度。 兹索伊多日名胜热
				工(smoothing process)的方式增加產品濃稠度。 該零售產品包裝於
				塑料容器中,淨含量 160 公克,且分為兩層- 下層為調製水果(草
				莓),而上層為白色乳製品。 第四個網灣別,及
0	1515 00	1	124	適用解釋準則一及六
2	1515. 90	1	增	Arachidonic Acid (ARA) Oil, in the form of a yellow or orange-yellow
				liquid at room temperature, obtained by fungus (Mortierella Alpina)
				fermentation from raw materials such as glucose. The oil has the
				following glyceride profile: 95 to 98 % triglyceride and 2 to 5 %
				diglycerides and monoglycerides. The profile of the main fatty acids of
				the product consists of polyunsaturated fatty acids, such as 40 to 45 %
				arachidonic acid and 0 to 15 % linoleic acid.
				This oil may be used as an ingredient in food, animal feed, medicine or
				cosmetics.
				Application of GIRs 1, 4 and 6.".
2	1515. 90	1	增	花生四烯酸油,於室溫時呈黃色或橙黃色液體,由原料(例如:葡萄
				糖)通過真菌發酵(Motierella Alpina)而成。此油品甘油脂比例:
				95~98%三酸甘油脂及 2~5%雙酸甘油脂與單酸甘油脂。此產品主要脂
				肪酸為多元不飽和脂肪酸,例如: $40~45\%$ 花生四烯酸及 $0~15\%$ 亞麻
				酸。此油品可用作食品、動物飼料、醫藥品或化妝品之原料。
				適用解釋準則一、四及六
3	2005.99	1	增	Pieces of red and green pepper fruits filled with cheese (feta
				cheese
				and fresh cheese), submerged in a liquid consisting of sunflower oil,
				garlic and spices. The product has the following composition, by weight:
				sunflower oil 40 %, cheese 35 % (17.5 % feta cheese and 17.5 % fresh
				cheese), pepper fruits (capsicum frutescens) 24 %, garlic and spices.
				the
				product is packaged in transparent containers of plastics with a net
				weight of 200 g.
				Application of GIRS 1 and 6.

項	HS CODE	編	增	貨品說明
次		號	修	
				Pull and the big plants where Senter
3	2005. 99	1	增	填充有乾酪(菲達乾酪及新鮮乾酪)之紅椒塊及綠椒塊,浸漬於含葵花
				油、大蒜及辛香料之液體。本產品之重量組成如下:葵花油 40%、乾
				酪 35%(17.5% 菲達乾酪及 17.5% 新鮮乾酪)、椒 (capsicum
				fructescens)24%、大蒜及辛香料,本產品包裝於透明塑膠容器,淨重
				200 公克。
4	2614.00	1	+⊷	適用解釋準則一及六
4	2014.00	1	增	Ilmenite ore, in the form of a black or dark brown powder containing ilmenite (> 90 %), magnetite (< 0.3 %), sulphate (< 0.1 %) and with a
				particle size < 45 µm for 99.5 % of the powder. It has not undergone
				any chemical treatment, only mechanical or physical operations such as
				grinding.
				The product is used as a weighing agent to increase the density in
				offshore well drilling.
				Application of GIR 1."
4	2614.00	1	增	<b>鈦鐵礦</b> ,呈黑/深褐色粉末狀,含有鈦鐵礦(>90%)、磁鐵礦(<0.3
				$\%$ )及硫酸鹽( $<0.1\%$ ), $99.5\%$ 的粉末顆粒尺寸 $<45\mu\mathrm{m}$ 。 它未經
				過任何化學處理,僅以機械或物理形式進行機械處理,例如碾磨。在
				海上油氣井鑽探過程中,該產品用以增加(鑽井液)密度的增重劑。
				適用解釋準則一
5	3002. 15	2	增	Diagnostic kit for detecting the Zika virus consisting of an ELISA
				(enzyme-linked immunosorbent assay) test kit that provides a
				semiquantitative in vitro assay for human antibodies of the immunoglobulin
				class IgM against Zika virus in serum.
				The product consists of the following components:  (i) Microplate wells coated with recombinant pen structural protein (NS1) of
				(i) Microplate wells coated with recombinant non-structural protein (NS1) of Zika virus, in the form of 12 microplate strips each containing 8 individual
				·
				break-off wells in a frame; (ii) Calibrator (IgM, human); (iii) Positive control (IgM, human);
				(iv) Negative control (IgM, human);

項次	HS CODE	編號	增修	貨品說明
				(v) Enzyme conjugate peroxidase-labelled anti-human IgM (goat); (vi) Sample buffer containing IgG/RF-Absorbent (Anti-human IgG antibody preparation obtained from goat); (vii) Wash buffer; (viii) Chromogen/substrate solution TMB/H <sub>2</sub> O <sub>2</sub> ; (ix) Stop solution 0.5 M sulphuric acid; (x) Protective foil; (xi) Test instruction; and (xii) Quality control certificate. In the first reaction step, diluted patient samples are incubated in the wells. In the case of positive samples, specific IgM (also IgA and IgG) antibodies will bind to the antigens. To detect the bound antibodies, a second incubation is carried out using an enzyme-labelled anti-human IgM (enzyme conjugate) catalysing a colour reaction. The kit is suitable for the serodiagnosis of acute and past Zika virus infections.  Application of GIRs 1, 3 (b) and 6. See also Opinion 3822.00/1.".
5	3002.15	2	增	檢測茲卡病毒診斷試劑組,由酵素免疫分析試劑組(ELISA)組成,為半定量體外檢測血清中抵抗茲卡病毒的免疫球蛋白IgM人類抗體。產品包含下列組成: (i) 將塗佈有茲卡病毒重組非結構蛋白(NSI)的微板孔排列於框架中,12個微板孔條並排,每個孔條含有8個獨立的分離孔; (ii) 校準品(IgM,人類); (iii) 陽性對照(IgM,人類); (iv) 陰性對照(IgM,人類); (v) 酵素結合物過氧化物酶標記抗人類IgM(山羊); (vi) 含有IgG / RF吸收劑(由山羊獲得的抗人類IgG抗體製劑)的樣品緩衝液; (vii) 清洗緩衝液; (vii) 為此溶液 0.5M硫酸; (x) 保護箔; (xi) 終此溶液 0.5M硫酸; (x) 保護箔; (xi) 檢測說明;及 (xii) 品管證書 在第一反應階段,將稀釋的患者樣品在孔中恆溫培育。若是陽性樣品,特定的IgM(IgA和IgG亦同)抗體將與抗原結合。為了檢測結合的抗體,會進行第二次恆溫培育,使用酶標記抗人類IgM(酵素結合物)進行催化顯色反應。 該試劑組適用於急性和已感染茲卡病毒的血清學診斷。

項	HS CODE	編	增	貨品說明
次		號	修	
				適用解釋準則一、三(乙)及六
				亦參見意見 3822.00/1
6	3002.15	3	增	Diagnostic kit for detecting the Chikungunya virus consisting of a ELISA (enzyme-linked immunosorbent assay) test kit that provides a semi quantitative in vitro assay for human antibodies of the immunoglobulin
				class IgM against chikungunya virus in serum or plasma for the diagnosis of chikungunya fever, and differential diagnosis of haemorrhagic fever.
				The product consists of the following components:
				(i) Microplate wells coated with recombinant chikungunya virus antigens, in the form of 12 microplate strips each containing 8 individual break-off wells in a frame;
				(ii) Calibrator (IgM, human);
				(iii) Positive control (IgM, human);
				(iv) Negative control (IgM, human);
				(v) Enzyme conjugate peroxidase-labelled anti-human IgM (goat),
				(vi) Sample buffer containing IgG/RF-Absorbent (Anti-human IgG antibody
				preparation obtained from goat);
				(vii) Wash buffer;
				(viii) Chromogen/substrate solution TMB/H2O2;
				(ix) Stop solution 0.5 M sulphuric acid;
				(x) Protective foil;
				(xi) Test instruction; and
				(xii) Quality control certificate.
				In the first reaction step, diluted patient samples are incubated in the wells.
				In the case of positive samples, specific IgM (also IgA and IgG) antibodies
				will bind to the antigens. To detect the bound antibodies, a second
				incubation is carried out using an enzyme-labelled anti-human IgM (enzyme conjugate) catalysing a colour reaction.
				Application of GIRs 1, 3 (b) and 6.
				See also Opinion 3822.00/1.".
6	3002.15	3	増	檢測屈公病毒診斷試劑組,由酵素免疫分析試劑組(ELISA)組成,
				為半定量體外測定血清或血漿中抵抗屈公病毒的免疫球蛋白IgM人類
				抗體,以供屈公熱及出血熱的鑑別診斷。
				產品包含下列組成:
				(i) 將塗佈有重組屈公病毒抗原的微板孔排列於框架中, 12 個微板
				孔條並排,每個孔條含有8個獨立的分離孔;
				(ii) 校準品(IgM,人類);
				(iii) 陽性對照(IgM,人類);
				(iv) 陰性對照(IgM,人類);

項次	HS CODE	編號	增修	貨品說明
				(v) 酵素結合物過氧化物酶標記抗人類IgM(山羊); (vi) 含有IgG / RF吸收劑(由山羊獲得的抗人類IgG抗體製劑) 的樣品緩衝液; (vii) 清洗緩衝液; (vii) 色原體/基質溶液(TMB/H <sub>2</sub> O <sub>2</sub> ); (ix) 終止溶液 0.5M硫酸; (x) 保護箔; (xi) 檢測說明;及 (xii) 品管證書 在第一反應階段,將稀釋的患者樣品在孔中恆溫培育。若是陽性樣品,特定的IgM (IgA和IgG亦同)抗體將與抗原結合。為了檢測結合的抗體,須進行第二次恆溫培育,並使用酶標記抗人類IgM (酵素結合物)會催化顯色反應。 適用解釋準則一、三(乙)及六亦參見意見 3822.00/1
7	3004.90	6	增	Bone graft substitute, in granular form, recommended for filling bone defects and bone augmentation in, for example, regenerative dentistry, such as for implantology, periodontology, and for reconstitution of the alveolar ridge of the jaw.  The product only consists of hydroxyapatite which is a composite of an inorganic nature from the group of calcium orthophosphates. The product is put up in packings for retail sale.  Application of GIRs 1 and 6.".
7	3004.90	6	增	骨移植替代物,顆粒狀,用於填充骨缺損和骨質增加,例如,牙周治療及重建下顎的齒槽脊等再生牙醫學所用之移植。該產品僅包含由具正磷酸鈣基團所衍化之氫氧基磷灰石所組成,後者為無機性之複合物。該產品(一般)裝入零售包裝。 適用解釋準則一及六
8	3602.00	1	增	Prepared explosive, consisting of dense, and very pure (non-porous), white, high-quality granules, containing: ammonium nitrate: 98 % min. (nitrogen content: 34 % min.), magnesium nitrate: 1.0 % - 1.6 % and combustible material: 0.2 % max.  This product is emulsified in inert mineral oils, and is intended for use as an explosive.

項次	HS CODE	編號	增修	貨品說明
7		<i>3</i> ))	19	
				It is put up in 1250 kg sacks.
				Application of GIR 1.
8	3602.00	1	增	調製炸藥,為緻密、非常純(非多孔性)、白色、高品質的顆粒,含 硝酸銨:至少98%(氮含量:至少34%),硝酸鎂:1.0%-1.6%及 可燃材料:最多0.2%。 本產品在惰性礦物油中乳化,且供作炸藥使用。 包裝為1250公斤袋裝。 適用解釋準則一
9	3602.00	2	增	Prepared explosive consisting of white, porous granules, containing: ammonium nitrate: 98 % min. (nitrogen content: 34 % min.), combustible material: 0.2 % max and a coating agent: 0.1 % max.  This product is the base material for the manufacture of ANFO (Ammonium Nitrate Fuel Oil), used for civil explosives (mining or civil engineering sites).  It is put up in 1250 kg sacks.  Application of GIR 1."
9	3602.00	2	增	調製炸藥,為白色、多孔性顆粒,含硝酸銨:至少98%(氮含量:至少34%),可燃材料:最多0.2%及塗層劑:最多0.1%。本產品是製造ANFO(硝酸銨燃料油)的基料,供作民用炸藥使用(採礦或土木工程場所)。 包裝為1250公斤袋裝。 適用解釋準則一
10	3808. 93	1	增	Intermediate preparation for herbicides, in the form of a brown, clear to slightly turbid aqueous solution containing paraquat dichloride (N,N'-dimethyl-4,4'-bipyridinium dichloride) (44.16-48.58 %), an emetic (PP796: max. 0.1 %) and colouring matter. The preparation requires further compounding to produce ready-made products. The product is presented in drums or in bulk.  Application of GIRs 1 (Note 1 (a) to Chapter 38) and 6.".
10	3808. 93	1	增	除草劑中間體調製品,呈一種棕色澄清至微混濁的水溶液型態,含有二氯巴拉刈(即N,N'-dimethyl-4,4'-bipyridinium dichloride) (44.16-48.58%)、催吐劑(PP796: max. 0.1%)及著色料,該項調製品需進一步調配生產為成品,以桶裝或散裝形式呈現。 適用解釋準則一(第38章章註一(甲))及六

項	HS CODE	編	增	貨品說明
次		號	修	A 11 10 7
11	3814.00	1	增	Organic solvent presented as a colorless, clear, homogenous liquid without solid contaminations, containing: xylene (88.23 %), toluene (0.55 %), methyl isobutyl ketone (7.68 %) and other products (3.50 %). It is used for breeding mastics, primers, paints, varnishes, adhesives, etc. It is presented in barrels of 20 liters. Application of GIR 1.".
11	3814.00	1	增	有機溶劑呈無色透明均勻液體,無固體不純物,含有:二甲苯(88.23%),甲苯(0.55%),甲基異丁基酮(7.68%)和其他產品(3.50%)。 它用於生產灰泥(breeding mastics),底漆,油漆,凡立水,黏合劑等。 以20升的桶裝形式包裝。 適用解釋準則一
12	3822.00	1	增	Diagnostic kit for detecting the Zika virus consisting of an in vitro assay based on the quantitative detection of Zika virus RNA through reverse transcription followed by real-time polymerase chain reaction (RT-PCR). The product consists of the following components:  (i) PCR Solution: Primer, probe, TRIS-HCI;  (ii) Mix Taq: Polymerase, dNTPs, MgCl2;  (iii) Mix Buffer: TRIS-HCI;  (iv) PCR Solution CI: Primer, probe, TRIS-HCI;  (v) Internal Control: Plasmid, TRIS-HCI;  (vi) Negative Control: TRIS-HCI;  (vii) Standard A (2 x 105 copies/µL): Plasmid, TRIS-HCI, EDTA;  (viii) Diluent: TRIS-HCI, EDTA;  (ix) Water: DNase/RNase free water; and  (x) Usage instructions (manual).  The product should be used with RNA samples extracted from serum, plasma, urine, cerebrospinal fluid and amniotic fluid.  The RT-PCR method is used to amplify the pathogen RNA. A thermocycler for RT-PCR is used to amplify and detect the fluorescent probe. Software calculates the Zika Virus RNA concentration, expressed in copies/µL, using the standard curve generated from the quantitative standard, contained in the kit.  Application of GIRs 1 and 3 (b).

項	HS CODE	編	增	貨品説明
次		號	修	
12	3822.00	1	增	用於檢測茲卡病毒的診斷試劑組,由一種基於即時反轉錄聚合酶鏈反應(RT-PCR)之定量檢測茲卡病毒 RNA 的體外試驗組成。該產品由以下組件組成: (i)聚合酶鏈鎖反應溶液(PCR Solution):引子(Primer),探針(probe),三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1); (ii) Mix Taq:聚合酶(Polymerase),去氧核糖核苷三磷酸(dNTPs),氯化鎂(MgCl₂); (iii) 混合緩衝液:三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1); (iv) PCR 溶液 CI:引子(Primer),探針(probe),三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1); (v)內部對照:質體(Plasmid),三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1); (vi)陰性對照:三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1); (vi)內標準品 A (2×105 copies/μL):質體(Plasmid),三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1); (vii) 標準品 A (2×105 copies/μL):質體(Plasmid),三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1); (vii) 稀釋劑:三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1),乙二胺四乙酸(EDTA); (viii)稀釋劑:三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1),乙二胺四乙酸(EDTA); (viii)稀釋劑:三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1),乙二胺四乙酸(EDTA); (viii)稀釋劑:三羟甲基氨基甲烷鹽酸鹽(TRIS-HC1),乙二胺四乙酸(EDTA);
13	3924. 90	6	增	Shower set (pipes, hand shower, shower head, round soap support, washer with filter, chromed hose, water divert and all the parts needed for the functioning of the shower) put up together in the same packaging for retail sale. Some of these parts are made of plastics and others are made of metal. The plastic shower head imparts the essential character to the set.  Application of GIRs 1, 3 (b) and 6.  Parts made of plastics:  Shower head  Slider

項次	HS CODE	編號	增修	貨品說明
				Parts made of metal:
				Bar (pipe)  Water diverter  (which diverts water between the hand shower and the shower head)  Chromed hose (Tube of plastics coated with metal to strengthen)
13	3924. 90	6	增	淋浴組件(管、手持蓮蓬頭、蓮蓬頭、圓形肥皂支架、含濾器墊圈、 鍍鉻軟管、水分流器及淋浴功能所需的所有零件),置於同一包裝中 供零售。本組合零件有些由塑膠製成,其他則由金屬製。塑膠蓮蓬頭 為本組件之主要特徵。 適用解釋準則一、三(乙)及六
14	4420. 90	1	增	<b>Table top art easel,</b> containing a drawer for holding art supplies.  Measuring 10 cm in height (when folded) x 40 cm in width x 38 cm in depth; it holds canvases or panels up to 86 cm high.
				Application of GIRs 1 and 6.
14	4420. 90	1	增	桌面藝術畫架,包含可放置藝術用具的抽屜,規格為 10 公分高(折疊時)×40 公分寬×38 公分深;並可放置高度達86 公分的畫布或畫板。
15	8303.00	1	增	適用解釋準則一及六  Safe, made of steel, designed to protect valuables, equipped with a programmable electronic keypad lock and indicator panel as well as a lock for an override key. The external dimensions are 200 x 310 x 200 mm and the internal dimensions are 198 x 308 x 140 mm (H x W x D). The safe weighs 4.5 kg, the door is 3 mm thick and the body is 1 mm thick. A dial on the front door positions two one-way sliding bolts (20 mm thick) into place. There are pre-drilled holes at the bottom and back to fix the safe to the floor or wall. It is intended for

項	HS CODE	編	增	貨品說明
次		號	修	A 11 00 14
				home and business use.
				Application of GIR 1.
15	8303.00	1	增	保險箱,鋼鐵製,設計用作保護貴重物品,配備可編程電子鍵盤鎖、 指示面板及可用鑰匙開啟的主鎖。外部尺寸為20×31×20公分, 內部尺寸為19.8×30.8×14.0公分(高×寬×深)。 保險箱重 4.5公斤,門厚0.3公分,壁厚0.1公分。前門上有一個轉盤,可將 兩個單向滑動栓(2公分厚)定位。底部和後部有預鑽孔,可將保險 箱固定在地板或牆壁上。適於家庭和商業用途。 適用解釋準則一
16	8303.00	2	增	Safe, made of steel, designed to protect valuables, equipped with a programmable electronic keypad lock and indicator panel as well as a lock for an override key. The external dimensions are 250 x 350 x 250 mm and the internal dimensions are 248 x 348 x 190 mm (H x W x D). The safe weighs 6 kg, the door is 3 mm thick and the body is 1 mm thick. A dial on the front door positions two one-way sliding bolts (20 mm thick) into place. There are pre-drilled holes at the bottom and back to fix the safe to the floor or wall. It is intended for home and business use.  Application of GIR 1.

項次	HS CODE	編號	增修	貨品說明
16	8303.00	2	增	保險箱,鋼鐵製,設計用作保護貴重物品,配備可編程電子鍵盤鎖、 指示面板及可用鑰匙開啟的主鎖。外部尺寸為 25 × 35 × 25 公分, 內部尺寸為 24.8 × 34.8 × 19.0 公分(高 × 寬 × 深)。保險箱重 6 公斤,門厚 0.3 公分,壁厚 0.1 公分。前門上有一個轉盤,可將兩個 單向滑動栓 (2 公分厚) 定位。底部和後部有預鑽孔,可將保險箱固 定在地板或牆壁上。適於家庭和商業用途。 適用解釋準則一
17	8479.89	8	增	Handheld machine, used for removing dirt and stains on clothes which have been moistened. The machine contains a horn which vibrates at ultrasonic speed creating micro-bubbles. The bursting force of these bubbles assists in removing dirt and stains.  Application of GIRs 1 and 6
17	8479.89	8	增	手持式機器,用於清除濕衣上之污垢及污漬。該機器含有 1 個喇叭可以超音波頻率振動以產生微小氣泡。這些氣泡的爆裂力有助於去除污垢及污漬。 適用解釋準則一及六
18	8509.80	1	增	Handheld machine, operated by a small electric motor, used for prewashing clothes to remove stains. The machine subjects the stains to a combination of water and detergent, followed by a patting action.  Dimensions (W x D x H) 46 x 46 x 166 mm, weight 200 g.  Application of GIRs 1 (Note 4 (b) to Chapter 85) and 6.

項次	HS CODE	編號	增修	貨品說明
				HANDY WASHER
18	8509.80	1	增	手持式機器,以小型電動機運作,用於預洗衣服以去除污渍。該機器
				使用水跟清潔劑的混合液將污漬浸溼,再利用拍打方式清潔。 尺寸 (寬 × 深 × 高)4.6 × 4.6 × 16.6 公分,重 200 公克。
				·本田知經》作品 (竹 OE 本本
19	8541. 29	2	增	insulated Gate Bipolar Transistor (IGBT) module, (dimensions: 62 mm x 106 mm x 36 mm) containing 1 IGBT, 1 diode in anti-parallel connection to the transistor in order to protect the transistor from the damage caused by reverse current when the transistor is turned off, and several electrodes. These components are interconnected by aluminium wires and enclosed in a plastic casing.  The functions of the product are: amplification, oscillation, frequency conversion, and switching of electrical current. The product regulates current and voltage in high-power applications and is capable of handling high current throughput. The voltage rating is 1200 V and the current rating is 400 A. It can be used in various applications, such as lighting and heating, motion control applications, electric fans, control of electric pumps, etc.  Application of GIRs 1 and 6.

支       態       修         19       8541.29       2       增 <b>经蛛附雙極性電晶體(IGBT)模組(</b> 尺寸 6.2×10.6×3.6 公分),由 1 IGBT 電晶體、1 個與 IGBT 電晶體及向並聯之二極體(用以保護電)免外關閉時被反向電流發展,這時其壞 2.20 以 3.20 以 4.00 以 7.10 以	項	HS CODE	編	增	化口2010
IGBT 電晶體、1 個與 IGBT 電晶體反向並聯之二極體(用以保護電息 免於關閉時被反向電流損壞)及多個電極組成,這些元件以銘線相違接並封裝在塑料外裁中。該產品之功能為放大、振盪、頻率轉換及電流切換,在高功率應別 1200V、400A、可用於各種應用,例如照明及加熱、運動控制應用電扇、電動系控制等。  Bicycle components, presented together and unassembled, suite for the same model of bicycle, not including all of the parts necessary assemble a finished bicycle, with the following configuration: - Frame; - Fork; - Handlebar; - Brake levers; - Stem; - Grip; - Complete crank set; - Shifter(s); - Brake mechanism/brakes; - BB part; - Saddle; - Seat post; - Chain wheel.  Application of GIRs 1 and 2(a).  20 8712.00 1 增 同時進口未組裝之腳踏車零件,適用於相同型號之腳踏車,不包括配完整腳踏車所需之所有零件,具有以下配置: - 車架; - 前又; - 手把; - 熟車把; - 龍頭; - 提把;		no core			貝而說明
Bicycle components, presented together and unassembled, suite for the same model of bicycle, not including all of the parts necessary assemble a finished bicycle, with the following configuration: - Frame; - Fork; - Handlebar; - Brake levers; - Stem; - Grip; - Complete crank set; - Shifter(s); - Brake mechanism/brakes; - BB part; - Saddle; - Seat post; - Chain wheel.    Application of GIRs 1 and 2(a).   Application of GIRs 2 and 2(a).   The part of the parts is necessary assembled, suite for the same model of bicycle, not including all of the parts necessary assemble a finished bicycle, not including all of the parts necessary assembled, suite for the same model of bicycle, not including all of the parts necessary assemble a finished bicycle, not including all of the parts necessary assemble a finished bicycle, not including all of the parts necessary assemble a finished bicycle, not including all of the parts necessary assemble a finished bicycle, not including all of the parts necessary assemble a finished bicycle, not including all of the parts necessary assemble a finished bicycle, not including all of the parts necessary assemble a finished bicycle, with the following configuration: - Frame; - Brake levers; - Stem; - Complete crank set; - Shifter(s); - Brake levers; - Stem; - Complete crank set; - Shifter(s); - Brake levers; - Stem; - Complete crank set; - Shifter(s); - Brake levers; - Stem; - Complete crank set; - Shifter(s); - Brake levers; - Stem; - Grip; - Complete crank set; - Shifter(s); - Brake levers; - Stem; - Grip; - Complete crank set; - Stem; - Grip; - Complete crank set; - Stem; - Grip; - Complete crank set; - Shifter(s); - Brake levers; - Stem; - Grip; - Complete crank set; - Shifter(s);	19	8541. 29	2	增	該產品之功能為放大、振盪、頻率轉換及電流切換,在高功率應用中 調節電流及電壓,具大電流處理能力,額定電壓、額定電流分別為 1200V、400A,可用於各種應用,例如照明及加熱、運動控制應用、 電扇、電動泵控制等。
20 8712.00 1 增 同時進口未組裝之腳踏車零件,適用於相同型號之腳踏車,不包括配完整腳踏車所需之所有零件,具有以下配置: - 車架; - 前叉; - 手把; - 煞車把; - 龍頭; - 握把;	20	8712.00	1	增	Bicycle components, presented together and unassembled, suitable for the same model of bicycle, not including all of the parts necessary to assemble a finished bicycle, with the following configuration:  - Frame;  - Fork;  - Handlebar;  - Brake levers;  - Stem;  - Grip;  - Complete crank set;  - Shifter(s);  - Brake mechanism/brakes;  - BB part;  - Saddle;  - Seat post;  - Chain wheel.
- 元登之曲柄組; - 變速撥桿; - 煞車機構/煞車器;	20	8712.00	1	增	同時進口未組裝之腳踏車零件,適用於相同型號之腳踏車,不包括裝配完整腳踏車所需之所有零件,具有以下配置: - 車架; - 前叉; - 手把; - 煞車把; - 龍頭; - 握把; - 完整之曲柄組; - 變速撥桿;

項次	HS CODE	編號	增修	貨品說明
		*****	,,	- 座墊;
				<u>/                                   </u>
				/王 D ,
				適用解釋準則一及二(甲)
21	8712.00	2	增	Bicycle components, presented together and unassembled, suitable
				for the same model of bicycle, not including all of the parts necessary to
				assemble a finished bicycle, with the following configuration :
				- Frame;
				- Fork;
				- Handlebar;
				- Stem (connecting the fork and handlebar);
				- Brake and gear levers and cables;
				- Brakes;
				- Crank arms;
				- Crank set;
				- Chain ring;
				- Chain ring bolts;
				- Front derailleur;
				- Seat post clamp.
0.1	0710 00	0	124	Application of GIRs 1 and 2(a).
21	8712.00	2	增	同時進口未組裝之腳踏車零件,適用於相同型號之腳踏車,不包括裝
				配完整腳踏車所需之所有零件,具有以下配置: - 車架;
				- 平示, - 前叉;
				1 元
				- 煞車把及煞車線;
				- 煞車器;
				- 曲柄臂;
				- 曲柄組;
				- 鏈環;
				- 鏈環螺栓;
				- 前變速器;
				- 座管夾。
				適用解釋準則一及二(甲)
22	8712.00	3	增	Bicycle components, presented together and unassembled, suitable
				for the same model of bicycle, not including all of the parts necessary to
				assemble a finished bicycle, with the following configuration :
				- Frame;
				- Fork;

項次	HS CODE	編號	增修	貨品說明
				- Handlebar;
				- Stem (connecting the fork and handlebar);
				- Brake handles and cables.
				Application of GIRs 1 and 2(a).
22	8712.00	3	增	<b>同時進口未組裝之腳踏車零件</b> ,適用於相同型號之腳踏車,不包括裝
				配完整腳踏車所需之所有零件,具有以下配置:
				- 車架;
				- 前叉;
				- 手把;
				- 龍頭;
				- 煞車把及煞車線;
				適用解釋準則一及二(甲)
23	9004.90	1	增	Virtual reality headset (VR headset) designed to be connected to
				and used with a specific type of mobile phone. In the common
				housing resembling goggles, the product incorporates the following main
				components :
				- an internal Central Processing Unit (CPU);
				- a pair of convex lenses to magnify the image of mobile phone's screen;
				- a focus wheel to adjust the position of magnifying lenses;
				- a key to control the volume of a mobile phone;
				- two micro-USB connectors to connect external power source and the mobile phone;
				- an accelerometer sensor and a gyro sensor for tracking the movement of user's head:
				- a proximity sensor to switch on/off mobile phone's screen;
				- a touch pad to control a mobile phone.
				The product is equipped with a flap holder for placing the mobile phone
				and holding it by its screen directly in front of the user's eyes. When a
				` ,
				headset can also be used to control the use of certain other functions
				, , , , , , , , , , , , , , , , , , , ,
				specific application is installed on the mobile phone and the mobile phone is connected to the headset, the built-in magnifying lenses allow the use to see a stereoscopic view of the mobile phone screen, which displays two, almost the same, side-by-side images. In addition, it also allows to control running of the application on the mobile phone by detecting the movements of the user's head (tilting and turning) in real time and transmitting the information, over the CPU of the headset, to the main board of the mobile phone. The touch pad and control keys of the

項次	HS CODE	編號	增修	貨品說明
23	9004. 90	1	增	設計供連接特定類型手機使用之虛擬實境頭套,具有類似護目鏡之外形,該產品主要包括以下零件: -內建中央處理器(CPU); -一對可放大手機螢幕影像之凸透鏡; -可調整放大鏡位置之焦距旋鈕; -手機音量控制鍵; -兩個 micro-USB 連接器,供接外接電源及手機; -可追蹤使用者頭部動作狀態之加速度感測器及陀螺儀; -可開/關手機螢幕之近接感測器; -控制手機之觸控板。 該貨品配備放置手機之支架,可使手機螢幕影像直接呈現於使用者眼前。手機安裝特定應用程式後與頭套連接,該頭套內建之放大透鏡可讓手機螢幕影像以立體形式供使用者觀看,該立體效果係以兩個幾乎相同影像並排所形成。另外,該貨品透過即時偵測使用者頭部動作狀態(傾斜及旋轉),並透過頭套之 CPU 傳送資訊予手機內主機,以控制手機應用程式的運行。頭套之觸控板及控制鍵亦可控制手機其他特定功能(例如:音量等)。
24	9506. 91	2	增	適用解釋準則一及六  Skipping rope, consisting of a solid core 5 mm PVC cord, approximately 3 m long, that can be used on any surface (concrete, pavement, wood flooring, etc.), and two handles made of plastics. The cord attaches at a 90° angle. The skipping rope is intended to be used for physical exercise.  Application of GIRs 1 and 6.

項次	HS CODE	編號	增修	貨品說明
24	9506. 91	2	增	跳繩,由直徑 0.5公分長度約 3公尺(10 英呎)之 PVC 實心繩子,及 2個塑膠手把組成。該跳繩可在任何平面上(如:混泥土、人行道、木質地板等)使用,繩子與把手以 90 度角連接。該貨品主要係供健身運動用。 適用解釋準則一及六
25	9620.00	2	增	Wireless "selfie-stick" made of steel, with a handle, a power switch and a charging port on one end and a mount on the other end. A smartphone can be mounted on it with an adjustable holder. It can be paired with a smartphone's operating system via an open wireless technology standard, e.g., Bluetooth®. Self-portrait photographs are taken by pressing the button on the stick. To take wider angle image photographs, the stick can be extended from 25 to 102 cm and the head offers rotation. It can also be used with digital cameras.  Application of GIRs 1 and 3 (b).
25	9620.00	2	增	鋼鐵材質之無線自拍棒,具有握把,自拍棒一端設有電源開關及充電孔,另一端為手機支架,可透過一可調整之裝置安裝智慧型手機。此透過公開的無線技術標準(如:藍芽)可與智慧型手機操作系統配對。按壓自拍棒上之按鍵即可自拍。為了得到廣角效果,自拍棒長度可以由25公分延伸至102公分,頭部並可旋轉。也可搭配數位相機使用。 適用於解釋準則一及三(乙)